



SUPER SONIC ATF TYPE A

Automatic Transmission Fluid

PRODUCT DATA

PROPERTIES

SUPER SONIC ATF TYPE A is a multipurpose transmission fluid, designed for use in automatic gear boxes, where GM Type a suffix A or DX I are quoted. **SUPER SONIC ATF TYPE A** can also be used in many power shift transmissions, Industrial torque converters and manual transmissions, where a low viscosity fluid is specified

PERFORMANCE FEATURES AND BENEFITS

- Exceptional low temperature fluidity.
- Excellent resistance to oxidation and high thermal stability
- Durability of friction characteristics and wear protection.
- Protection against rust and corrosion, and good seal compatibility

RECOMMENDATIONS / SPECIFICATIONS

SUPER SONIC ATF TYPE A meets or exceeds the requirements of GM type A suffix A or DX I as well as Allison C3 specifications.

Typical Data	Unit	Test Method	Results
Density at 15°C	g/cm ³	ASTM D4052	0.865
Colour	-	VISUAL	RED
Viscosity at 100°C	mm ² /s	ASTM D445	7.5
Flash Point	°C	ASTM D92	200 min

Note: The information contained herein is subject to change without notification. Typical Properties may vary slightly.



Packing :1USQ | 1L | 4L | 208L

ATL/C-PDS/06/NGT/0*, 02.01.17, Page 1/1
* supersedes all previous versions

Health and Safety: This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.