



SUPER SONIC RADIATOR COOLANT

Ready to Use Engine Coolant

PRODUCT DATA

PROPERTIES

SUPER SONIC RADIATOR COOLANT - 33% is a specially formulated ready to use engine coolant, for both petrol and diesel engines. It is mixture of mono-ethylene glycol and selected chemical agents to provide outstanding all round protection.

PERFORMANCE FEATURES AND BENEFITS

- Effective engine cooling without boiling.
- A clean cooling system with protection from sludge and scale deposits.
- Protection against corrosion of the alloys used in the cooling system of modern vehicle.
- Protection against frost.
- Prevention against electrolysis.
- Protection against cavitations corrosion.
- Efficient lubrication of water pumps.
- Compatibility with rubbers.

FILLING INSTRUCTION

Coolant should not be further diluted while using in the system or when topping-up. Prior to filling with the Coolant, cooling system should be properly cleaned and cleared of all blockages and suspended rust and dirt in the system should be flushed with clean water. In a clean cooling system, Coolant will deliver optimum performance and protection for up to one year upon which the system should be drained and refilled with Coolant.

RECOMMENDATIONS / SPECIFICATIONS

Meets BS 6580(1992) (UK) Standards, JIS K 2234-97, Class 2 Juliik

SUPER SONIC RADIATOR COOLANT meets the requirements of Major European Manufacturers.

Typical Characteristics

SR. NO	TEST PARAMETERS	TEST METHOD	TYPICAL
1)	Density @ 15°C gm/cm3	ASTM D1298	1.08
2)	pH	ASTM D 1121	9.0
3)	Reflux boiling point °C	ASTM D 1120	106
4)	Freezing point °C	ASTM D 1117	-18
5)	Concentration % wt		33.00

Note: The information contained herein is subject to change without notification. Typical Properties may vary slightly.



PACKING : 208 L | 5L | 4L | 1L