



SUPER SONIC HYDRAULIC OILS AW

Very High Performance Anti-Wear Hydraulic Oils

PRODUCT DATA

DESCRIPTION

SUPER SONIC HYDRAULIC OILS AW are supreme performance anti-wear hydraulic oils designed to satisfy a wide range of hydraulic equipment requirements. They were developed to meet the stringent requirements of severe hydraulic systems using high pressure, high output pumps as well as handling the critical requirements of other hydraulic system components such as close clearance servo-valves and the high accuracy numerically controlled (NC) machine tools. Formulated with high quality base oils and a super-stabilized additive system that neutralizes the formation of corrosive materials & designed to work with systems operating under severe conditions where high levels of antiwear and film strength protection are needed, yet they are formulated to work where non-antiwear hydraulic oils are generally recommended.

APPLICATIONS

SUPER SONIC HYDRAULIC OILS AW are designed to give excellent protection in mobile and stationary hydraulic vane-, piston-, and gear-type pumps and in high-performance industrial applications as well as in environmentally sensitive areas. Suitable for use in all kind of hydraulic systems running under the most difficult conditions, such as in machine tools, mould injection machines, presses and other industrial or mobile equipment. Also used in many other applications, where a universal high performance anti-wear lubricant is the first choice: low charged gears, sliding and roller bearings, air compressors, servo-motors and control systems equipped with fine filtration systems.

PROPERTIES

SUPER SONIC HYDRAULIC OILS AW series provide outstanding oxidation resistance allowing extension of oil and filter change intervals. Their high level of anti-wear properties and excellent film strength characteristics result in exceptional equipment performance that not only results in fewer breakdowns but helps improve production capacity. Their controlled demulsibility permits the oils to work well in systems contaminated with small amounts of water yet readily separate large amounts of water.

PRODUCT BENEFITS

- High protection against wear insuring maximum equipment life.
- Superior thermal stability avoiding formation of sludge even at high temperature.
- Very good oxidation stability ensuring a long service life of the fluid
- Remarkable filterability even in the presence of water
 - Excellent hydrolytic stability avoiding filter blocking.
- Excellent protection against rust and corrosion.
- Good anti-foam and air release properties by using silicon free components.
- Good demulsibility ensuring rapid water separation
- Reduced maintenance and operating costs
- Quality reserve maintains performance features even under severe service conditions and extended drain intervals

RECOMMENDATIONS / SPECIFICATIONS

International Standards : AFNOR NF E 48-603 HM, ISO 6743/4 HM, DIN 51524 P2 HLP, CINCINNATI MILACRON P68, P69, P70
Meets or exceeds : VICKERS M-2950S, -I-286, DENISON HFO, HF1, HF2 (T6H20C), HUSKY HS 207

ISO Viscosity Grade	32	68
Appearance, Visual	B&C	B&C
Density at 15°C, g/ml, ASTM D4052	0.875	0.884
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	32	68
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	5.42	8.77
Viscosity Index, ASTM D2270	102	100
Flash Point(COC), °C, ASTM D92	210	228
Pour Point, °C, ASTM D97	-24	-21
FZG 4-Square Load Support, DIN 51354, Fail Stage	12	12
Copper strip corrosion, 3 hrs @ 100°C, ASTM D130	1B	1B
Rust protection Proc B, ASTM D665	PASS	PASS



Packing : 5 | 20 | 25 | 208 L

ATL/C-PDS/HF/0018/01*, 02.01.19, Page 1/1
* supersedes all previous versions

Health and Safety: This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.