



SUPER SONIC PETROL/DIESEL ENGINE OIL SAE 40 API CC/SC

High Performance Mono-grade Engine Oils

PRODUCT DATA

PROPERTIES

SUPER SONIC PETROL/DIESEL ENGINE OIL SAE 40 API CC/SC is high performance monograde diesel engine oil formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in inter-cooled, turbo-charged engines operating under severe on and off-highway conditions. SUPER SONIC PETROL/DIESEL ENGINE OIL SAE 40 API CC/SC can be used in a wide range of applications where a monograde lubricant is recommended.

FEATURES AND BENEFITS

- Excellent protection against oil thickening
- Excellent protection against sludge build-up
- Reduced high temperature engine deposits
- Reduces wear due to advanced base oils
- Excellent protection against ring sticking

APPLICATION

Formulated for use in naturally aspirated and turbo-charged diesel powered equipment, On-highway light and heavy-duty trucking & Off-highway industries including: construction, mining, quarrying & agriculture.

RECOMMENDATIONS / SPECIFICATIONS

API: CC/SC

Meets or exceeds: MTU Type 2, Mercedes Benz 228.2, Allison C-4, MAN 270

Typical Data	Unit	Test Method	Results
SAE Grade			40
Density at 15°C	g/cm ³	ASTM D4052	0.88
Viscosity at 40°C	mm ² /s	ASTM D445	125.3
Viscosity at 100°C	mm ² /s	ASTM D445	14.6
Viscosity Index	-	ASTM D2270	117
Flash Point	°C	ASTM D92	200 min
Pour Point	°C	ASTM D97	-9

Note: The information contained herein is subject to change without notification. Typical Properties may vary slightly.



Packing : 700|800ml,1|2|3|4|5|6.5|7|8|16|18|20|25|200|205|208|210L,1|5|20|55 USQ

ATL/C-PDS/02/NGT/0*, 02.01.17, Page 1/1
* supersedes all previous versions

Health and Safety: This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.