



# SUPER SONIC 2T OIL

## 2-STROKE MOTOR OIL

### PRODUCT DATA

#### DESCRIPTION

**SUPER SONIC 2T OIL** is high performance, low smoke, low ash two stroke engine oil made from the latest synthetic additives and premium base oils. It exceeds many manufacturer requirements including API TC, JASO FC & ISO EG-C requirements

#### APPLICATIONS

**SUPER SONIC 2T OIL** is suitable for use in all types of two stroke engines including motorcycles, mopeds and scooters that use either a premix or oil injection system. It is suitable for use in two stroke chainsaws, brush cutters, lawn mowers and other gardening equipment in domestic and industrial use. It is also suitable for stationary engines and industrial power units. **SUPER SONIC 2T OILS** should not be used in outboard engines.

#### PERFORMANCE FEATURES AND BENEFITS

- Reliable and consistent performance
- Self-mixing with leaded and unleaded petrol
- Low Smoke, Low Ash formulation
- Extends engine life
- Good anti-scoff properties
- Mixes readily with petrol
- Meets the requirements of leading manufacturers
- Enhanced lubricity and detergency, keeping engines clean
- Maximizes spark plug life
- Reduces exhaust port blockages
- Keeps piston rings free from deposits
- Suitable both for all oil-injection and premix systems

#### RECOMMENDATIONS / SPECIFICATIONS

Industry Specifications: API TC, JASO FD, ISO EG-D

	TEST VALUE
Density at 15°C, g/ml, ASTM D4052	0.872
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s, ASTM D445	63.12
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s, ASTM D445	8.9
Viscosity Index, ASTM D2270	116
Flash Point(COC), °C, ASTM D92	122
Pour Point, °C, ASTM D97	-21
Colour	RED

Note: The information contained herein is subject to change without notification. Typical Properties may vary slightly.



**Packing : 25ml | 500ml | 800ml | 1L**