



# SUPER SONIC 4T MOTOR OIL SAE 20W-40 API SL/CF

High Performance Conventional 4-Stroke Motor Oil

## PRODUCT DATA

### PROPERTIES

SUPER SONIC 4T MOTOR OIL SAE 20W-40 API SL/CF is high performance conventional four-stroke motorcycle engine oils designed specifically for motorcycles to meet the requirements that automotive oils are not designed to handle. Premium base oils and advanced additives are used to meet special properties for proper performance and protection of wet clutch system, high RPMs and temperatures, and metals found in motorcycles to bring out the best in your machine.

### APPLICATIONS

SUPER SONIC 4T MOTOR OIL SAE 20W-40 API SL/CF is primarily intended for general use in all types of four-stroke motorcycles and engines. It is suitable for all makes of 4-stroke bikes, both carburetor and fuel injected where API SL (or below) and JASO MA or MA2 are recommended.

### PROPERTIES

SUPER SONIC 4T MOTOR OIL SAE 20W-40 API SL/CF combines highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection. Specially formulated to provide outstanding, durable protection under severe high-torque, high-stress conditions when motorcycle engines operate at extremely high temperatures, causing viscosity and thermal breakdown of motor oil. SUPER SONIC 4T MOTOR OIL SAE 20W-40 API SL/CF is engineered to provide maximum protection against viscosity and thermal breakdown.

### PERFORMANCE FEATURES AND BENEFITS

- Shear Stability
- Film Strength
- Excellent Corrosion Protection
- Provides exceptional protection for ATVs
- For use in 4-Stroke Motorcycles, including Cruisers and Off-Road Motorcycles
- High RPM, High Temperature Performance
- Helps extend engine life
- Broad viscosity range
- Wet Clutch Protection
- Maximum Horsepower
- Good wear protection
- Advanced Cleaning
- Year round engine protection and performance
- Meets or exceeds manufacturer's warranty requirements

### RECOMMENDATIONS / SPECIFICATIONS

International Standards : API SL, SL/CF, SJ, SG, SG/CD, SF, JASO MA2

Recommended for vehicles such as Aprilia, BMW, Honda, Kawasaki, KTM, Moto Guzzi, Suzuki, V Moto, Yamaha, Cagiva, Can-Am, Ducati, Hyosung, Triumph and more

Viscosity Grade, SAE J300	20W-40
Density at 15°C, g/ml, ASTM D4052	0.88
Cold Cranking Viscosity(CCS), mPa s, ASTM D5293	6000@-15°C
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s, ASTM D445	125
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s, ASTM D445	15.1
Viscosity Index, ASTM D2270	124
Flash Point(COC), °C, ASTM D92	230
Pour Point, °C, ASTM D97	-27
Total Base Number, mg KOH/g, ASTM D2896	8.0

Note: The information contained herein is subject to change without notification. Typical Properties may vary slightly.



Packing : 25ml | 500ml | 800ml | 1L

NGT/C-PDS/AL/014D/0\*, 02.01.19, Page 1/1  
\* supersedes all previous versions

**Health and Safety:** This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.