



SUPER SONIC SUPER 4T SAE 20W-50 API SL/CF

High Performance Passenger Car Motor Oil

PRODUCT DATA

PROPERTIES

SUPER SONIC SUPER 4T SAE 20W-50 API SL/CF is premium quality engine oil developed to the highest standards of lubricant quality, reliability and dependable protection. SUPER SONIC SUPER 4T SAE 20W-50 API SL/CF is multigrade gasoline engine oil formulated from selected base fluids for use in passenger car and light truck engines requiring API SL/CF or lower performance lubricants and where SAE 20W-50 viscosity grading is acceptable.

PERFORMANCE FEATURES AND BENEFITS

- Protects engines under all operating conditions by providing excellent wear control.
- High thermal stability and oxidation resistance
- Excellent protection against in-service oil degradation
- Metallic detergent and ashless dispersant additive system maintains high power and performance.
- Low oil consumption.
- Excellent control of piston and ring deposits under high temperature conditions.

APPLICATION

Specially formulated for use in naturally aspirated gasoline engines in passenger cars and light commercial vehicles, four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils.

RECOMMENDATIONS / SPECIFICATIONS

International Standards: API SL/CF, ACEA: A3/B3

Recommended for use: Ford, GM, PSA, BMW, VW, Audi and Mercedes-Benz

Typical Data	Unit	Test Method	Results
SAE Grade			20W-50
Density at 15°C	g/cm ³	ASTM D4052	0.890
Viscosity at 40°C	mm ² /s	ASTM D445	153.2
Viscosity at 100°C	mm ² /s	ASTM D445	17.7
Viscosity Index	-	ASTM D2270	121
Flash Point	°C	ASTM D92	236
Pour Point	°C	ASTM D97	-21

Note: The information contained herein is subject to change without notification. Typical Properties may vary slightly.



Packing : 700|800ml,1|2|3|4|5|6.5|7|8|16|18|20|25|200|205|208|210L,1|5|20|55 USQ

NGT/TDS/03/NGT/0*, 02.01.17, Page 1/1
* supersedes all previous versions

Health and Safety: This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute any special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.