

PRODUCT DATA SHEET

MOTRON - MOTOR ENGINE OIL 4T SAE 20W50 API SG/CD

PRODUCT NAME: MOTRON - MOTOR ENGINE OIL 4T SAE 20W50 API SG/CD

MOTRON Motor Engine Oil is a high range quality lubricant, specially formulated to meet the latest performance requirements of modern engines. It can be used in city, road, and highway, under extreme conditions in all seasons.

Application:

This product is suitable for use in automobile, gasoline, and diesel engines where the manufacturer recommends the following specifications: 4T SAE 20W50 API SG/CD

Performance Benefits

- Improved control of volatility and oil consumption
- Protects against soot, varnish, and sludge formation.
- Highly effective control over wear, corrosion, and rust
- Exceptional resistance to oxidation and foaming
- Excellent dispersive and detergent properties which ensure a clean engine.
- Improved protection during start-up by maintaining protective oil films.

Properties

Test Description	Test Method	Result(s)
Appearance	Visual	Clear & Bright
Color	ASTM-D1500	L2.5
Kinematic Viscosity @ 40 °C, cSt	ASTM-D445	182.2
Kinematic Viscosity @ 100 °C, cSt	ASTM-D445	20.18
Viscosity Index	ASTM-D2270	129
Pour Point, °C	ASTM-D97	-27
Flash Point (COC), °C	ASTM-D92	236
Density @ 15°C, kg/L	ASTM-D1298	0.8807
TBN, mgKOH/g	ASTM-D2896	7.29
Water in Petroleum Product	ASTM-D95	(-) ve
CCS @ -15°C, cP	ASTM-D5293	7850

LUBRICANTS - GREASES - SPECIALITY OIL

LUBRICANTS - GREASES - SPECIALITY OIL