



Roulez
en toute **Confiance**

PRODUCT DATA SHEET

MOTRON - MOTOR ENGINE OIL SAE 10W40 API SL/CF

PRODUCT NAME: MOTRON - MOTOR ENGINE OIL SAE 10W40 API SL/CF

MOTRON Motor Engine Oil is a high range quality lubricant, semi synthetic, specially formulated to meet the latest performance requirements of modern engines. It can be used in city, road and highway, under extreme conditions in all seasons.

Application

This product is suitable for use in automobile, gasoline and diesel engines where the manufacturer recommends the following specifications: SAE 10W40 API SL/CF.

Performance Benefits

- Very high lubricity to reduce friction
- Excellent oxidation stability
- Great protection against corrosion, rust and foam
- Very good wear-resistant properties resulting a perfect protection of the engine
- Excellent dispersive and detergent properties

Properties

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	2.0
Density @ 15 °C, kg/L	D-1298	0.8685
Viscosity @ 100 °C, cSt	D-445	14.75
Viscosity @ 40 °C, cSt	D-445	105.6
Viscosity index	D-2270	145
Flash Point, °C (COC)	D-92	216
Pour Point, °C	D-97	-32
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	6.5
CCS at -25°C (mPa.s)	D-5293	6280

LUBRICANTS - GREASES - SPECIALITY OIL