



**Roulez**  
en toute **Confiance**

---

## PRODUCT DATA SHEET

### MOTRON - MOTOR ENGINE OIL SAE 15 W40 API SL/CF

PRODUCT NAME: MOTRON - MOTOR ENGINE OIL SAE 15W40 API SL/CF

MOTRON Motor Engine Oil is a high range quality lubricant, semi synthetic, specially formulated to meet the latest performance requirements of modern engines. It can be used in city, road and highway, under extreme conditions in all seasons.

#### Application

This product is suitable for use in automobile, gasoline and diesel engines where the manufacturer recommends the following specifications: SAE 15W40 API SL/CF.

#### Performance Benefits

- Very high lubricity to reduce friction
- Excellent oxidation stability
- Great protection against corrosion, rust and foam
- Very good wear-resistant properties resulting a perfect protection of the engine
- Excellent dispersive and detergent properties

#### Properties

Test Description	Test Method	Result(s)
Appearance	Visual	Clear & Bright
Color	ASTM-D1500	2.0
Kinematic Viscosity @ 40 °C, cSt	ASTM-D445	120.1
Kinematic Viscosity @ 100 °C, cSt	ASTM-D445	15.24
Viscosity Index	ASTM-D2270	132
Pour Point, °C	ASTM-D97	-30
Flash Point (COC), °C	ASTM-D92	232
Density @ 15°C, kg/L	ASTM-D1298	0.8762
TBN, mgKOH/g	ASTM-D2896	8.73
Water in Petroleum Product	ASTM-D95	(-) ve
CCS @ -20°C, cP	ASTM-D5293	6050

---

**LUBRICANTS - GREASES - SPECIALITY OIL**